India's Best Transactional Terminal



COMTRANS

Handheld Computing Device





RUGGED & COMPACT Portable & Ergonomic Design. Weight Less Than 600gms



EASY TO INSTALL Multi Language Support. Multiple Print Formats. Multi Application Support.



WORKS 24 X 7 Continuous Fast Billing. Extended Battery Backup. Secured Data Storage.



ZERO MAINTENANCE Trouble Free Thermal Printer. Re-chargeable Li-ion Battery. Soft-touch Keypad.



SHAKE YOUR HANDS In-Built BAR CODE Scanner, GPRS, Camera, GPS, RFID Smart Card Reader.



EASY TO USE
User Friendly Operations.
Easy paper loading.
Audio & Visual Indications.



TRACK YOUR TRANSACTIONS

Customized reports. SMS/GPRS Communication.

APPLICATION AREAS



Retail



Warehouse



Manufacturing



Logistic



Parking Management



Cable TV Rentals



Health Care



Restaurants



Petrol Bunk



Banking & Finance



Transport



Van Sales / Delivery



Queue Busting



Entry Token Issue

COMTRANS

FEATURES & SPECIFICATIONS

Processor	Quad-Core ARM @ Cortex-A53 1.3GHz/512KB
Operating System	Android 6.0
NAND Flash Memory	8 GB
SDRAM	1 GB
MMC/SD Card Support	Micro SD Card Support Upto 64GB
Display Type	5"- HD 720x1280 Colour TFT
Touch Screen	Capacitive Touch Panal
Integrated printer	2" Thermal Printer
Key Pad Details	4 Keys
Finger Print (Optional)	Optical Finger print Sensor with Scanned area of 14x22(mm), Ceritified at Highest level: FIPS 201, MINEX FBI PIV IOS, STQC Approved Authentication device Morpho
RFID reader (Optional)	RFID Contactless Smart Card Reader/Writer- supports ISO/IEC 14443A (incl. Mifare, Desfire Family (EV1, 2K/4K/8K), ISO/IEC 14443B, Sony FeliCa and NFC - ISO/IEC 18092 standard
Barcode (Optional)	Sensor resolution of 1280 x 960 pixels, capture 1D and 2D bar codes in milliseconds, from high-resolution photos, to letter, legal, A4 and A5 documents that are fully searchable and editable
GPS (Optional)	High Sensitivity acquisition - 165 dBm with position accuracy lessthan 3 Meters and supports AGPS function.
Camera (Optional)	Upto 5 Mega Pixel Inbuilt Camera
USB Support	2 NOS (USB Type-A & Micro USB)
SAM Card (Optional)	Dual SAM Control of the Control of t
GPRS	26/36
Battery	7.4V/3350mAh Lithium Ion Battery with Protection circuit with fast charging time 3 to 4 hrs
Real Time Clock Part	In built RTC with 3V, Coin Lithium battery Cell for Backup
Buzzer	Mono BUZZER
Audio	1 Watt Speaker With Optional Mic
External Adapter	9V/2A External Adapter
Weight	> 550 gms